

## Comprehensive Scope 2 Monocular Head PLAN Objectives

Model # TU-19011CP / TU-19011CP-230



**Detailed Specifications (January 2014)** 

	T	Detailed Specifications (January 2014)
Head	Eyepieces	1– WF10x 19mm eyepiece with built-in coating for humidity and poor climate; 1 with pointer; all fixed to avoid loss and damage
	Eyepiece Tubes	1 – Variable adjustment ± 0.20x for varied eye strengths.
	Monocular View with 45°	1 45°Angle 360° rotation attached eyepieces comfortable student or teacher viewing
	incline	
Frame	Aluminum Single Cast	"Y" shape base for ideal research application
	Integrated Stow and Go	Retractable Handle for transport are integrated into the body of the unit.
	Handle™	
	Integrated storage	Storage compartment with built-in receptacle for the external power supply
	"Table Guard" protection	Base outlined with resilient polymer to avoid daily damage to the Microscope or the
	base	surrounding surfaces
	Illumination	Ken-A-Vision LED cool lighting source with very long life (12,000+ hours), on/off switch,
		and dimmer rheostat. On/off switch and dimmer are separate, dimmer rheostat is low
		position light control
	Power	USB compliant / IEC 62684:2011 charging system standardized on external USB
		to AC adapter 5V1A DC operation included or USB 2.0 computer port or
		backward compliant for legacy power supply 5.5V500mA; 7.5V800mA
Optics	Nose Piece	Reversed 4 hole nose piece with 4 position ball bearing action stop, 360 full rotation
	Objectives	3 – lead free, humidity and climate protected by special coating; manufactured
		according to DIN: PLAN Achromat 4x N.A. 0.10, PLAN Achromat 10x N.A. 0.25, PLAN
		Achromat 40x(S) N.A. 0.65 (with built-in spring action tip to avoid crushing of specimen),
Stago	Fixed Plain Stage w/Side	12cm x 12cm x 0.7cm modular attachment to frame 2 spring loaded clips for slides
Stage		12cm x 12cm x 0.7cm modular attachment to frame 2 spring loaded clips for slides
	Clips	
	Focus	Low position coaxial focus with left or right hand low drive control; with rotating
		mechanism and torque adjustment 1 coarse rotation from minimum to maximum stage
		height. Fine 0.002mm per unit scale mechanism, rubber grips on both fine and coarse
	10.	focus knobs; Fine focusing scale value 0.002mm
Optional upgrades	Viewing Head	Dual View with 30° incline opposing view (SC12DH)
		Compensation Free Binocular Head (SC12BH)
		Compensation Free Trinocular Head (SC12TH)
		Compensation Free Digital Monocular Head (SC12CMH2)
		Compensation Free Digital Binocular Head (SC12CBH2)
	Eyepiece	WF 16x, WF 20x
	Achromatic Objective	4x, 10x, 20x, 40x(S), 60x(S), 100x(S) Oil
	Plan Objective	20x, 60x(S), 100x(S) Oil
	Semi-Plan Objective	4x, 10x, 20x, 40x(S), 60x(S), 100x(S) Oil
	Illumination	Halogen bulb 6v/20W, Adjustable Brightness
Packing	Boxing	Two inner cartons in one outer carton
O antificant and	Protective Cover	Durable Clear Dust cover with Ken-A-Vision logo
	Weights and Dims	14lbs/6.4kgs - 20" X 16" X 13"/50.8cm X 40.64cm X 33.02cm
Certificates	Patents	Multiple Patents Pending
	Quality Certificates	ISO:90012000
	Local Certificates	CE, CSA, RoHS
	Warranty Guarantee	10 Years against manufacturing faults